

## Nylon Straight Butted Seam

Wire Size	Part No.	L	Terminal	I.D.
22-18	20081	.990	10080	.135
	20081E	.990	10080E	.135
16-14	20171	.990	10170	.155
	20171E	.990	10170E	.155
12-10	20311	1.070	10310	.205
	20311E	1.070	10310E	.205

## Nylon Flared Butted Seam

22-18	50081	.985	10080	.165
	50081E	.985	10080E	.165
16-14	50171	.985	10170	.195
	50171E	.985	10170E	.195
12-10	50311	1.070	10310	.270
	50311E	1.070	10310E	.270

## Nylon Flared Seamless

22-18	20083	.985	10083	.165
16-14	20173	.985	10173	.195
12-10	20313	1.070	10313	.270

## Nylon Straight Seamless

26-24	22403#	.757	12403	.080
22-18	20083S	.990	10083	.135
	20083LN	1.06	10083L	.135
16-14	20173S	.990	10173	.155
	20173LN	1.06	10173L	.155
	20173XLN	1.06	10173XL	.155
12-10	20313S	1.070	10313	.205
	20313LN	1.25	10313L	.205

8	20624N	1.500	10624	.260
6	20625N	1.780	10625	.340
4	20626N	1.980	10626	.430

## 4 Pc Nylon w/ Sleeve

22-18	30080	1.00	10080	.135
16-14	30170	1.00	10170	.155
12-10	30310	1.20	10310	.205
3 PC TOOL			20717	

## Cool Seal Nylon Butts

22-18	29083	1.00		
16-14	29173	1.00		
12-10	29313	1.20		

**Seals Out Moisture Causing Corrosion. A Heat-Less/Solderless Connection.**