

Uninsulated Butted Seam

Wire Size	Part No.	
22-18	UPT1#	
16-14	UPT2#	
12-10	UPT5#	
8	UPT8BZ Brazed#	
4	UPT25-15#	

Vinyl Insulated

Wire Size	Part No.	
22-18	PTV1# PTV1UL*	
16-14	PTV2# PTV2UL*	
12-10	PTV5# PTV5UL*	

2-Pc Nylon

Wire Size	Part No.	
22-18	PTN1#	
16-14	PTN2#	
12-10	PTN5#	
4	PTN25BZ#	

3-Pc Nylon w/ Sleeve

Wire Size	Part No.	
22-18	PT3N1#	
16-14	PT3N2#	
12-10	PT3N5#	

3 PC. TOOL 20717

Flags

Non Insulated

Wire Size	Part No.	Length	Tab Width	
22-18	12188#		.187	
	10188#		.250	
	10999	open	.250	
16-14	12189#		.187	
	10189#		.250#	
	10669		.250 (male)	
12-10	10190#		.250	
	10190B	open	.250	

Heat Shrink

Wire Size	Polyolefin Part No.	NYAX Part No.	Tab Width
22-18	42188	70188	.187
	40188		.250
16-14	42189	70189	.187
	40189		.250
12-10	40190	70190	.250

Nylon Insulated

Wire Size	Part No.	Length	Tab Width	
22-18	22188#	.53	.187	
	20188#	.58	.250	
	20188L#	.82	.250	
16-14	22189#	.53	.187	
	20189#	.58	.250	
	20189L#	.82	.250	
12-10	20190#	.68	.250	
	20190L#	.90	.250	

See Page 39 [Tool \(20594\)](#) for 22-18 and 16-14 and [Tool \(20704\)](#) for 16-14 and 12-10.

VOLTAGE RATINGS

Insulated Copper Terminals
 Insulated Brass Disconnects
 Tap Splices (16-10AWG)
 Tap Splices (18AWG)

600 volts MAX
 300 volts MAX
 32 volts MAX
 18 volts MAX