

3 TO 1	1/2" X 4'	23545-48B		23545-48R				
3 TO 1	3/4" X 4'	23550-48B		23550-48R				
3 TO 1	1" X 4'	23555-48B		23555-48R				
3 TO 1	1.25" X 4'	23560-48B						
3 TO 1	1.5" X 4'	23565-48B						
3 TO 1	2" X 4'	23570-48B						
<b>DUAL WALL ADHESIVE LINED</b>								
<b>RATIO</b>	<b>OD X LENGTH</b>	<b>BLACK</b>	<b>CLEAR</b>	<b>RED</b>				
3 TO 1	1/8" X 6"	23525-06B	23525-06C	23525-06R				
3 TO 1	3/16" X 6"	23530-06B	23530-06C	23530-06R				
3 TO 1	1/4" X 6"	23535-06B	23535-06C	23535-06R				
3 TO 1	3/8" X 6"	23540-06B	23540-06C	23540-06R				
3 TO 1	1/2" X 6"	23545-06B	23545-06C	23545-06R				
3 TO 1	3/4" X 6"	23550-06B	23550-06C	23550-06R				
3 TO 1	1" X 6"	23555-06B	23555-06C	23555-06R				
3 TO 1	1 1/4" X 6"	23560-06B	23560-06C	23560-06R				
3 TO 1	1 1/2" X 6"	23565-06B	23565-06C	23565-06R				
3 TO 1	2" X 6"	23570-06B	23570-06C	23570-06R				
<b>HEAVY WALL</b>								
3 TO 1	3/8" X 48"	23590-48B		23590-48R				
3 TO 1	3/4" X 6"	23591-06B		23591-06R				
3 TO 1	3/4" X 48"	23591-48B		23591-48R				

### SHRINK TUBING CHART

Tubing O.D.	Non Insulated	Vinyl/ Nylon	Copper Lugs	Heavy Duty Lugs	Battery Terminals
3/32"	26-24				
1/8"	22-18	26-24			
3/16"	16-14	22-18			
1/4"	12-10	16-14			
3/8"	8-6	12-10	8-6	8-4	
1/2"	4-2	8-6	4-1/0	1	4
3/4"	1/0-3/0	4-1/0	2/0-4/0	1/0-3/0	1-3/0
1"		2/0-3/0	250MCM	4/0	4/0

## Heat Shrink Box Kits



**Red & Black HS Box Kit**

Part No.:  
5990-74BR

6": (10) Black 1/8", (10) Red 1/8",  
 (10) Black 3/16", (10) Red 3/16",  
 (5) Black 1/4", (5) Red 1/4",  
 (4) Black 3/8", (4) Red 3/8",  
 (5) Black 1/2", (5) Red 1/2",  
 (3) Black 3/4", (3) Red 3/4"



**Black HS Box Kit**

Part No.:  
5990-62 BLACK

4": (20) 1/8", (20) 3/16", (10) 1/4",  
 (5) 3/8", (5) 1/2", (2) 3/4"  
 3:1 Shrink Ratio-UL & CUL.  
 Certified at 600V 125 degree C  
 temp. 90-120 degree C-UL FILE  
 E333465 RoHS Compliant



**Color HS Box Kit**

Part No.:  
5990-160 MULTI

4" Colors: Black, Blue, Clear, Green,  
 Red, White, Yellow  
 (60) 1/16", (35) 3/32", (25) 1/8",  
 (20) 3/16", (10) 1/4", (10) 3/8"  
 2:1 Shrink Ratio-UL & CUL.  
 Certified at 600V 125 degree C temp.  
 90-120 degree C-UL FILE E333465  
 RoHS Compliant



**Black HS Box Kit**

Part No.:  
5990-160 BLACK

4": (60) 1/16", (35) 3/32",  
 (25) 1/8", (20) 3/16", (10) 1/4", (10)  
 3/8"  
 2:1 Shrink Ratio-UL & CUL.  
 Certified at 600V 125 degree C temp.  
 90-120 degree C-UL FILE E333465  
 RoHS Compliant