

## Bare Seamless

Wire Size	Part No.
22-18	10647
16-14	10648
12-10	10649
8	10650
6	10651
4	10652
2	10653



\*Only one crimp needed to complete splice



## 2 Pc. Nylon

Wire Size	Part No.
22-18	20647N
16-14	20648N
12-10	20649N
8	20650N
6	20651N



## Vinyl Insulated

Wire Size	Part No.
22-18	20647
16-14	20648
12-10	20649
8	20650



## Heat Shrink

Wire Size	Part No.
22-18	40647
16-14	40648
12-10	40649
8	40650



# Adapters

## Double Male Single Female Brass

10664<sup>^</sup>  
10664 PLTD



## 3-Way Adapter Brass

10665  
10665 Plated



## Chair Adapter Brass

10667



## 2-Way Bullet Receptacle

10668



## Insulated Double Male 75°C 300 volts

10670  
10670-L



## Insulated Triple Male 75°C 300 volts max

10671



## ATO Fuse Tap Brass

10672  
10672-mini



## Glass Fuse Tap Brass

10673



All Adapters have .250 tabs, except the 2-Way Bullet Receptacle which has a .157 Tab

# Ferrule Wire Ends



Wire Size	Color	Part No.	Dimensions
22	White	10822+	.551 x .051 x .122
20	Blue	10820+	.551 x .061 x .130
18	Red	10818+	.551 x .061 x .138
16	Black	10816+	.551 x .083 x .157
14	Gray	10814+	.551 x .102 x .185
12	Orange	10812+	.669 x .134 x .213
10	Green	10810+	.787 x .161 x .272
6	Blue	10806 <sup>^</sup>	



\* Copper Ferrule with nylon insulation  
 Temp Range - 40° c up to 105° c



Crimps 22-10  
 Part # 20598  
 Length 9.3"